



LCMF 16, LCMF 30 - MP

	CW	CWTOLL	CWTOLU	INSL
	(mm)	(mm)	(mm)	(mm)
0316	3.00	-0.05	0.05	17.5
0416	4.00	-0.05	0.05	17.6
0516	5.00	-0.05	0.05	18.3
0616	6.00	-0.05	0.05	18.5
0830	8.00	-0.05	0.05	30.9




Valores de inicio adecuados para la velocidad de corte (vc), avance (f) y profundidad de corte (ap). Consulte nuestra APP Calculadora de mecanizado para obtener más cálculos.

Producto	RE	P			M			K			N			S			H		
		vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap
	(mm)	(m/min)	(mm/rev)	(mm)	(m/min)	(mm/rev)	(mm)	(m/min)	(mm/rev)	(mm)	(m/min)	(mm/rev)	(mm)	(m/min)	(mm/rev)	(mm)	(m/min)	(mm/rev)	(mm)



Geometría MP para torneado longitudinal y perfilado en copia, con corte continuo a interrumpido.

LCMF 0316MO-MP	T8330	1.5	190	0.30	0.8	110	0.27	0.8	180	0.30	0.8	—	—	—	—	—	—	—	—
LCMF 0416MO-MP	T8330	2.0	175	0.40	1.0	105	0.36	1.0	165	0.40	1.0	—	—	—	—	—	—	—	—
	T9325	2.0	220	0.40	1.0	130	0.36	1.0	205	0.40	1.0	—	—	—	—	—	—	—	—
LCMF 0516MO-MP	T8330	2.5	170	0.45	1.0	100	0.41	1.0	160	0.45	1.0	—	—	—	—	—	—	—	—
	T9325	2.5	205	0.45	1.0	120	0.41	1.0	190	0.45	1.0	—	—	—	—	—	—	—	—



Geometría MP para torneado longitudinal y perfilado en copia, con corte continuo a interrumpido.

LCMF 0616MO-MP	T8330	3.0	165	0.50	1.0	95	0.45	1.0	155	0.50	1.0	—	—	—	—	—	—	—	—
	T9325	3.0	200	0.50	1.0	120	0.45	1.0	190	0.50	1.0	—	—	—	—	—	—	—	—
LCMF 0830MO-MP	T8330	4.0	150	0.60	1.2	90	0.54	1.2	140	0.60	1.2	—	—	—	—	—	—	—	—